

# & Performance Series DVRs

The Performance Series DVRs meet all your requirements for quick and easy setup and operation.

The embedded Linux operating system provides ultimate reliability for 24/7 recording. Express search enables

the operator to quickly find the video evidence in times of urgent need. Web browser support enables remote live view and searching video stored in the DVR from a networked PC without having to load remote access software.



Honeywell Part Number	Storage	Audio Channels	Monitor Outputs	IPS Recorded	Recording Resolution NTSC	Remote Users (Simultaneous)	Alarm Inputs/Outputs
<b>16 Looping Video Channels DVR - 480 ips, Internal DVR-R/W and 2 USB Ports</b>							
HRDPX16D500	500 GB	16 Line Input/ 1 Line Output	Main: VGA-1 Main: BNC-1 Main: SVideo Spot: 3	480 ips CIF 240 ips 120 ips 4CIF	CIF: 352 x 240 2CIF: 704 x 240 4CIF: 704 x 480	Admin: 1 Watch & Search: 3	16/4
HRDPX16D1T	1 TB						
HRDPX16D2T	2 TB						
<b>16 Looping Video Channels DVR - 120 ips, Internal DVR-R/W and 2 USB Ports</b>							
HRDP16D250	250 GB	1 Line Input/ 1 Line Output	Main: VGA-1 Main: BNC-1 Main: SVideo Spot: 3	120 ips CIF 60 ips 2CIF 30 ips 4CIF	CIF: 352 x 240 2CIF: 704 x 240 4CIF: 704 x 480	Admin: 1 Watch & Search: 3	16/4
HRDP16D500	500 GB						
HRDP16D750	750 GB						
HRDP16D1000	1 TB						
<b>8 Looping Video Channels DVR - 120 ips, Internal DVR-R/W and 2 USB Ports</b>							
HRDP8D250	250 GB	1 Line Input/ 1 Line Output	Main: VGA-1 Main: BNC-1 Spot: 1	120 ips CIF 60 ips 2CIF 30 ips 4CIF	CIF: 352 x 240 2CIF: 704 x 240 4CIF: 704 x 480	Admin: 1 Watch & Search: 3	8/1
HRDP8D500	500 GB						
HRDP8D750	750 GB						
<b>4 Looping Video Channels DVR - 120 ips, Internal DVR-R/W and 2 USB Ports</b>							
HRDP4D250	250 GB	1 Line Input/ 1 Line Output	Main: VGA-1 Main: BNC-1 Spot: 1	120 ips CIF 60 ips 2CIF 30 ips 4CIF	CIF: 352 x 240 2CIF: 704 x 240 4CIF: 704 x 480	Admin: 1 Watch & Search: 3	4/1
HRDP4D500	500 GB						
<b>4 Video Channels DVR - 120 ips, 2 USB Ports</b>							
HRDP4F250	250 GB	4 Line Input/ 1 Line Output	Main: VGA-1 Main: BNC-1 Spot: 1	120 ips CIF 60 IPS 2CIF 30 IPS 4CIF	CIF: 352 X 240 2CIF: 704 X 240 4CIF: 704 X 480	Admin: 1 Watch & Search: 3	4/1

## Performance Series



EXPANDING OUR PRODUCT PORTFOLIO  
TO MEET YOUR EVERY NEED

Because performance matters

For more information:  
[www.honeywellvideo.com](http://www.honeywellvideo.com)

**Honeywell Security Group**  
Honeywell  
2700 Blankenbaker Pkwy, Suite 150  
Louisville, KY 40299  
1.800.796.CCTV (2288)  
[www.honeywell.com](http://www.honeywell.com)

**Honeywell**

**Honeywell**

L/PERFSRSB/D  
March 2010  
© 2010 Honeywell International Inc.



# Honeywell's Performance Series Cameras

## Because performance matters











No matter what performance you need in video surveillance, we've got the options you're looking for. We're rounding out our camera portfolio with a variety of indoor, outdoor and low light cameras that let you pick just the right one for virtually any application. The Performance Series cameras includes a wide range of high performing IR bullet cameras and mini-domes that are easy to install and even easier to use. Powered by 12 VDC, these cameras are armed with a 1/3" SONY Super HAD CCD image sensor that provides sharper image quality, so you see every detail when it counts. Plus, our cameras are competitively priced—giving you value from a partner you know and trust.

Honeywell's experience and commitment to innovation, combined with the quality and reliability of our integrated video systems, allows our customers to meet their existing and emerging security challenges. Whether you need the performance of IR illumination for low light environments or basic functionality for indoor or outdoor applications, Honeywell has a performer for you!

### Our Performance Series offers

- IR Bullet Cameras
- IR Indoor/Outdoor Rugged Mini-Domes
- IR Indoor Mini-Domes
- Indoor/Outdoor Rugged Mini-Domes
- Indoor Mini-Domes



	Honeywell Part Number	Description	Horizontal Resolution	S/N Ratio	Lens	Minimum Illumination	Illumination	IR LED Visible Range	Power Consumption	IP Rating
<b>IR Bullet Cameras</b>										
	<b>HB73</b>	Super High Res. True Day/Night, DNR	550 TVL	>50 dB (AGC Off)	DC Iris Vari-focal Lens (f=3.8~9.5 mm)	Day (0.3 lux), Night (0.00 lux, IR LED On)	18 IR LED (850 nm, 30°)	Max. 65 ft., 20m	Max. 4.2W/300mA	IP65
	<b>HB72B/W/S</b>	Super High Res. Day/Night	530 TVL	>48 dB (AGC Off)	Fixed Lens (f=4.3 mm)	Day (0.3 lux), Night (0.00 lux, IR LED On)	12 IR LED (850 nm, 30°)	Max. 50 ft., 15m	Max. 4.0W/300mA	IP65
	<b>HB71B/S</b>	Standard Res. Day/Night	380 TVL	>50 dB (AGC Off)	Fixed Lens (f=6.0 mm)	Day (0.1 lux), Night (0.00 lux, IR LED On)	34 IR LED (850 nm, 15° and 30° mixed)	Max. 95 ft., 30m	Max. 4.2W/300mA	IP65
	<b>HB70</b>	Standard Res. Day/Night	380 TVL	>48 dB (AGC Off)	Fixed Lens (f=4.3 mm)	Day (0.1 lux), Night (0.00 lux, IR LED On)	12 IR LED (850 nm, 30°)	Max. 50 ft., 15m	Max. 4.2W/300mA	IP65
<b>IR Indoor/Outdoor Rugged Mini-Domes</b>										
	<b>HD73</b>	Super High Res. True Day/Night	530 TVL	>48 dB (AGC Off)	DC Iris Vari-focal Lens (f=3.8~9.5 mm)	Day (0.3 lux), Night (0.00 lux, IR LED On)	20 IR LED (850 nm, 30°)	Max. 65 ft., 20m	Max. 4.5W/360mA	IP66
	<b>HD70</b>	Super High Res. Day/Night	550 TVL	>50 dB (AGC Off)	Fixed Lens (f=4.0 mm)	Day (0.3 lux), Night (0.00 lux, IR LED On)	24 IR LED (850 nm, 30°)	Max. 50 ft., 15m	Max. 5W/400mA	IP66
<b>IR Indoor Mini-Domes</b>										
	<b>HD61</b>	Standard Res. Day/Night	380 TVL	>48 dB (AGC Off)	Manual Varifocal Lens (f=4~9 mm)	Day (0.3 lux), Night (0.00 lux, IR LED On)	20 IR LED (850 nm, 30°)	Max. 65 ft., 20m	Max. 4.5W/360mA	
	<b>HD60</b>	Standard Res. Day/Night	380 TVL	>48 dB (AGC Off)	Fixed Lens (f=4.0 mm)	Day (0.1 lux), Night (0.00 lux, IR LED On)	24 IR LED (850 nm, 30°)	Max. 50 ft., 15m	Max. 5W/400mA	
<b>Indoor/Outdoor Rugged Mini-Domes</b>										
	<b>HD51</b>	Super High Res. Color	550 TVL	>50 dB (AGC Off)	DC Iris Vari-focal Lens (f=4~9 mm)	0.3 lux			Max. 3W/250mA	IP66
	<b>HD50</b>	Super High Res. Color	530 TVL	>48 dB (AGC Off)	Fixed Lens (f=3.8 mm)	0.3 lux			Max. 1.8W/150mA	IP66
<b>Indoor Mini-Domes</b>										
	<b>HD40</b>	Standard Res. Color	380 TVL	>48 dB (AGC Off)	Fixed Lens (f=3.8 mm)	0.1 lux			Max. 1.8W/150mA	

Get your Performance Series Cameras and DVRs today! To order or for more information, call Inside Sales Sensor Team at 1.800.796.CCTV (2288).