

P032,VAR2=B3 Half cylinder - system P0

Mechanical locking cylinders

Half cylinder



Locking cylinders form the core element of secure locking systems and represent IKON's core competency. The product range meets challenging security requirements with sophisticated solutions. High-quality IKON locking cylinders provide high protection against intruders. Standard equipment in this respect includes anti-drilling devices, security cards and panic functions. Patented profiles are a direct result of decades of experience gained in precision engineering and are effectively equipped against even the latest intrusion or burglary techniques. These features include innovative VECTOR profiles and the IKON reversible key profile WSW-W10.


Area of Application

Half cylinders are frequently used where doors and gates are only locked on one side (e.g. garage doors, cellar doors and tool sheds). They are however also used in lifts, alarm systems and other auxiliary security systems (e.g. lockable window handles).


ASSA ABLOY

ASSA ABLOY, the global leader
in door opening solutions

P032,VAR2=B3 Half cylinder - system P0



Product description

- 5 pin tumblers
- Brass cylinder
- Standard finish, satin nickel-plated (OF=MV)
- Basic cylinder length A (L=30) other installation lengths available
- Standard cam position (SST=8x45°) - reversible
- Other cam positions (SST=30°, 8x30°, 90-270, 270-90, 0-90, 180-90)
- Available for individual lockings and locking systems
- Available for individual locking with standard locking (AA=NML), without security card
- Key with square metal head
- Tapered cylinder core head with reinforced key guide
- Core pins made of special wear-resistant bronze
- Cam made of break and corrosion-resistant sinter metal

Accessories/Individual parts

- Cylinder fixing screw 1149

Compatible ASSA ABLOY products

- Maintenance spray 8511

Scope of delivery

- 1 half cylinder
- 3 nickel silver keys
- 1 cylinder fixing screw M5 x 85mm



P032,VAR2=B3 Half cylinder - system P0

Current profiles for individual locking

Profile (PR=)	Standard profile N1.	Standard profile AEP10
Profile version	70	71
With security card included	No	Yes
Drilling protection (AB=)	optional	0+1
Emergency device (GE=)	optional	optional
Locking wave (SW=)	-	-
VdS class	-	-
RAL quality symbol	-	-
DIN class	-	-
Modular system (GBK=)	-	-
Additional lateral pins	-	-
Factory-keyed profile/Client profile	Factory-keyed profile	Factory-keyed profile
Key head shape	Square	Square



ASSA ABLOY
Sicherheitstechnik GmbH
Goerzallee 299
14167 Berlin
berlin@assaabloy.de
Tel. +4930 8106-0
Fax +4930 8106-26 00
www.assaabloy.de

ASSA ABLOY, the global leader
in door opening solutions