

PC51 Double cylinder CH - system P0

Mechanical locking cylinders

Double cylinder

Closes on one side (A), dummy on other side (B)



Locking cylinders form the core element of secure locking systems and represent IKON's core competency. The product range meets challenging security requirements with sophisticated solutions. High-quality IKON locking cylinders provide high protection against intruders. Standard equipment in this respect includes anti-drilling devices, security cards and panic functions. Patented profiles are a direct result of decades of experience gained in precision engineering and are effectively equipped against even the latest intrusion or burglary techniques. These features include innovative VECTOR profiles and the IKON reversible key profile WSW-W10.

Area of Application


Double cylinders with a Swiss round profile that can only be actuated from one side are generally used for entrance doors with a lower security requirement, or due to building conditions. IKON double cylinders are available in a variety of lengths to meet the needs and requirements of every installation situation. There is a choice of different designs. It goes without saying that you can also obtain several keyed alike locking cylinders, so that only one key is required for several doors.

IKON
ASSA ABLOY

ASSA ABLOY, the global leader
in door opening solutions

PC51 Double cylinder CH - system P0

Closes on one side (A), dummy on other side (B)



Product description

- 5 pin tumblers
- Brass cylinder
- 22mm diameter
- Standard finish, satin nickel-plated (OF=MV)
- Other surfaces: brass, mat brushed (OF=MG), polished brass (OF=MP)
- Basic cylinder length 61mm (C) - A/B (L=30/30) other installation lengths available
- Available for individual lockings and locking systems
- Drilling protection (AB=), emergency equipment (GE=), additional lateral scanning, security card depending on profile (PR=)
- Key with square metal head
- Tapered cylinder core head with reinforced key guide
- Cam made of break and corrosion-resistant sinter metal
- Core pins made of special wear-resistant bronze

Accessories/Individual parts

- Cylinder fixing screw 1149

Compatible ASSA ABLOY products

- Maintenance spray 8511

Scope of delivery

- 1 double cylinder
- 3 nickel silver keys
- 1 cylinder fixing screw M5 x 85mm



PC51 Double cylinder CH - system P0

Closes on one side (A), dummy on other side (B)

Current profiles for individual locking

Profile (PR=)	Standard profile N1.
Profile version	70
With security card	No
included	
Drilling protection (AB=)	optional
Emergency device (GE=)	optional
Locking wave (SW=)	-
VdS class	-
RAL quality symbol	-
DIN class	-
Modular system (GBK=)	-
Additional lateral pins	-
Factory-keyed profile/Client profile	Factory-keyed profile
Key head shape	Square

ASSA ABLOY
Sicherheitstechnik GmbH
Goerzallee 299
14167 Berlin
berlin@assaabloy.de
Tel. +4930 8106-0
Fax +4930 8106-26 00
www.assaabloy.de



ASSA ABLOY, the global leader
in door opening solutions