## S6B3,VAR=PAN Steel security fitting with cylinder cover - handle/handle

**Door fittings** 

**Special security fittings** 



Short backplate for panic and fire doors



IKON provides a broad selection of security fittings and escutcheons, with or without cylinder covers. The wide range of IKON fittings is suitable for house and apartment doors, interior and exterior doors and doors made of all conventional materials. It encompasses a variety of handle fittings, a broad range of anodised finishes and colours and a quality spectrum ranging from solid aluminium fittings to premium security steel fittings. Solid steel with drilling protection and internal screw fittings with high tensile resistance form a practically impervious shield for locking cylinders.


### **Area of Application**

These IKON security fittings are approved for use on fire doors conforming to DIN 18273 but not suitable for use on metal frame doors.



# S6B3,VAR=PAN Steel security fitting with cylinder cover - handle/handle

Short backplate for panic and fire doors



### **Product description**

- IKON steel security fittings for metal frame doors correspond to IKON series S4.. steel security fittings in terms of essential design and quality characteristics
- Suitable for use on panic doors as well as Freeway® emergency exit locks with DIN EN 179
- Distance 92mm
- 9mm spindle
- Material internal backplate: solid steel, matt chrome-plated
- Material external backplate: solid steel, hardened, matt chrome-plated
- External backplate thickness 12mm Internal backplate thickness 6mm
- Available for door thicknesses (thickness in mm): 30-40 (TS=P40-XAM21-XIM18); 37-47

(TS=P47-XAM25-XIM21); 44-54

(TS=P54-XAM28-XIM25); 51-61

(TS=P61-XAM32-XIM28); 58-68

(TS=P68-XAM35-XIM32); 65-75

(TS=P75-XAM39-XIM35); 72-82

(TS=P82-XAM42-XIM39); 79-89

TS=P89-XAM46-XIM42; 86-96

(TS=P96-XAM49-XIM46); 93-103

(TS=P103-XAM53-XIM49)

- I Handle anodised aluminium with steel core
- Handle colour matchs escutcheons
- Standard finish silver (FB=F1)
- Fixing of external backplate from inside with 2 highly traction-resistant through bolts (1 x M8, 1 x M6) in strengthened threaded bushes with drilling protection
- Double screwed joint
- No DIN or VdS certification
- The fitting variant VAR=PAN is a fire security fitting checked by MPA Dortmund.
- Fittings with the variant VAR=PAN in combination with certified locks of the company ASSA ABLOY Sicherheitstechnik GmbH are allowed for DIN 179



emergency exit locks.

## Compatible ASSA ABLOY products

- Double cylinder .551
- Double cylinder .531

## Scope of delivery

I Set with fixing material



# S6B3,VAR=PAN Steel security fitting with cylinder cover - handle/handle

Short backplate for panic and fire doors

Article-No.	FB=	TS=	AUS=
S6B3,VAR=PAN	F1		P
	F1		ZA0-IKON

