

System SK6 - Vector profile

1st security level

Suitable for system types GH, H, KHZ, Z, ZUE

Mechanical locking cylinders

New profiles for locking systems



Product description

- 6 spring-loaded pin tumblers complying with DIN EN 1303 and DIN 18252 = protection against unauthorised opening
- Paracentric key profile = unlocking security
- Protected key profile with security card = Key security
- DIN EN 1303, lock security class 6
- DIN EN 1303, intrusion resistance class 0*, optionally available with extraction protection class 2 (* intrusion resistance class 2 is achieved with AB=1, 2 in accordance with a security fitting of the class ES2 ZA)
- Optional DIN testing, class 82, with drilling protection, optionally available with extraction protection
- Optional VdS approval, class B, with drilling protection, optionally available with extraction protection
- Special profile design and pin combination provide a high degree protection against lock picking and "key bumping"
- Key with square metal head

Premium -quality profile, special class SK6 with 6 active spring-loaded pin tumblers. Key profiling is arranged parallel to the spine of the key. The respective profile features are therefore arranged horizontally and bevelled relative to each other and form a characteristic pair. This special arrangement of profile features obstructs manual opening techniques significantly and provides a high degree of unlocking and scanning security as well as protection against unauthorised opening when compared to conventional key profiles.

ZIKON
ASSA ABLOY

ASSA ABLOY, the global leader
in door opening solutions